JOWA USA

MetriGuard Tank Monitor



Description:

The MetriGuard Tank Monitor is a 24 tank (maximum) instrument that directly interfaces with JOWA USA's Metritape level and level/temperature sensors that provide reliability and accuracy, even in demanding cargo tanks. The MetriGuard Tank Monitor can be configured with a single or dual multiplexer for 32 or 64 input channels. It converts the sensor output into calibrated data and sends serial data to the customer's equipment. A small internal display is used for setup and calibration.

Approved intrinsic safety barrier circuits are integral to the MetriGuard and allow it to be used with sensors in hazardous areas.

Features:

- Modbus RTU Output of tank level and or temperature
- Provides one Loss of Power relay

Specifications:

Calibration and Set-Up: Via included

panel or RS-232 connector

Enclosure Size:

32 Channel: 406 mm W x 610 mm H x 175 mm D [16.0" W x 24.0" H x 6.9" D]

64 Channel: 508 mm W x 610 mm H x 175 mm D [20.0" W x 24.0" H x 6.9" D]

Inputs: AC Power: 90 to 135 VAC or 180 to

270 VAC, 50/60 Hz

Sensor type: Metritape

Metritape Sensor Length: 1 - 35 meters


[3 - 115 feet]

Outputs: Modbus RTU Output of tank level and or temperature; RS232, RS485 2 or 4

wire

MetriGuard Tank Monitor

Block Diagram of Sample System:



Disclaimer:
This is not a specification and all information is provided in good faith. Since conditions of use are beyond the control of JOWA USA, Inc., the information contained herein is without warranty, whether express, implied or otherwise. Final determination as to the suitability, merchantability or fitness of any information, material or product for a particular purpose, or any patent infringement, is the sole responsibility of the user. JOWA USA, Inc. does not assume liability for injury arising from the use of the information, material or product, and assumes no liability for any damages, whether direct, indirect, consequential, special, incidental, punitive or otherwise. For additional information regarding JOWA USA, Inc.'s limited warranty, refer to the Terms and Conditions that are currently in effect.

JOWA USA

JOWA USA, Inc. 59 Porter Road Littleton, MA 01460-1431 USA

Tel: +1 978-486-9800 Toll free: 800-861-1560

Fax: + 1 978-486-0170 E-mail: info@jowa-usa.com